

FLATRACK

!!! Внутренние размеры и грузоподъемность контейнеров разных изготовителей может незначительно отличаться



Ratings¹

Maximum Gross Weight

Tare Weight

Payload

Concentrated load over center 2 metre

20' Flatrack

34,000 kg (74,950 lb.)

2,740 kg (6,040 lb.)

31,260 kg (68,860 lb.)

20,000 kg (44,090 lb.)

40' Flatrack

45,000 kg (99,207 lb.)

4,795 kg (10,570 lb.)

40,205 kg (88,627 lb.)

25,400 kg (55,997 lb.)

External Dimensions²

Length

6,058 mm (19'-10½")

12,192 mm (40'-0")

Width

2,438 mm (8'-0")

2,438 mm (8'-0")

Height

2,591 mm (8'-6")

2,591 mm (8'-6")

(Folded) Height

370 mm (14½")

641 mm (25¼")

Internal Dimensions

Length

5,613 mm (18'-4 15/16")

11,762 mm (38'-7 1/16")

Width

2,218 mm (7'-3 3/8")

2,378 mm (7'-9 5/8")

Height

2,213 mm (7'-3 1/8")

1,960 mm (6'-5 3/16")

Test Loads

Stacking

86,400 kg (190,447 lb.)

86,400 kg (190,447 lb.)

Transverse Racking

15,240 kg (33,600 lb.)

15,240 kg (33,600 lb.)

Longitudinal Racking

7,620 kg (16,800 lb.)

7,620 kg (16,800 lb.)

Floor Strength

7,260 kg (16,000 lb.)

7,260 kg (16,000 lb.)

Lashing Points

5,000 kg (11,025 lb.)

5,000 kg (11,025 lb.)

¹Seven empty units can be stacked into a 20' X 8'-6" module

²Four empty units can be stacked into a 40' X 8'-6" module